

## Maximum permitted weights and dimensions, goods transport Greece

<b>Height</b>	4.00m
<b>Width</b>	
Motor vehicle/trailer	2.55m
Refrigerated vehicle	2.60m
<b>Length</b>	
Motor vehicle	12.00m
Trailer	12.00m
Articulated vehicle	16.50m <sup>1</sup>
Road train	18.75m <sup>2</sup>
Car transporter	
· empty	18.75m
· loaded	18.75m
<b>Weight per axle</b>	
single axle (fixed)	10.0t
drive axle	11.5t
tandem axle of motor vehicle, provided the norms applicable to a single axle are respected; with a distance between the axles of	
· less than 1.00m	11.5t
· 1.00m to <1.30m	16.0t
· 1.30m to <1.80m	18.0t
· 1.30m to <1.80m if the drive axle is equipped with twin wheels and pneumatic suspension or equivalent	19.0t
tandem axle (non-drive) of trailer/semi-trailer, provided the norms applicable to a single axle are respected; with a distance between the axles of	
· less than 1.00m	11.0t
· 1.00m to <1.30m	16.0t
· 1.30m to <1.80m	18.0t
· 1.80m or more	20.0t
tridem axle (non-drive) of trailer/semi-trailer, provided the norms applicable to a tandem axle are respected; with a distance between the axles of	
· 1.30m or less	21.0t
· >1.30m to 1.40m	24.0t
<b>Maximum permitted weight</b>	
Motor vehicle	
· with 2 axles	18.0t
· with 3 axles	25.0t
· with 3 axles, if the drive axle has twin tyres and pneumatic suspension or equivalent	26.0t
· with 4 axles, two of which are steering axles, if the drive axle has twin tyres and pneumatic suspension or equivalent, and if the MPW does not exceed 5t/m of length between the two outermost axles	32.0t
Trailer	
· with 2 axles	18.0t
· with 3 axles	24.0t
Articulated vehicle	
· with 4 axles (2+2), where the distance between the axles of the semi-trailer is from 1.3m to 1.8m	36.0t
· with 4 axles (2+2), where the distance between the axles of the semi-trailer is over 1.8m, provided that the MPW of the tractor (18t) and of the tandem axle of the semi-trailer (20t) are respected, and that the drive axle is equipped with twin wheels and pneumatic suspension or equivalent	38.0t

· with 5/6 axles	<b>42.0t</b>
· with 5/6 axles (3+2/3) for the transport of 40' ISO containers	44.0t
Road train	
· with 4 axles (2+2)	36.0t
· with 5/6 axles	<b>42.0t</b>

<sup>1</sup> if the maximum distance between the axis of the fifth-wheel king pin and the rear of the semi-trailer is 12m, and the distance measured horizontally between the axis of the fifth-wheel king pin and any point at the front of the semi-trailer does not exceed 2.04m; otherwise, the maximum length is 15.50m

<sup>2</sup> if the length of the consignment is 15.65m and the length of the cabin 2.35m; otherwise, the maximum length is 18m

**Source:** OFAE, March 2015