

## Maximum permitted weights and dimensions, goods transport Turkey

<b>Height</b>	4.00m
<b>Width</b>	
Motor vehicle/trailer	2.55m
Refrigerated vehicle	2.60m
<b>Length</b>	
Motor vehicle	
· with 2 axles	12.00m
· with 3 axles or more	12.00m
Articulated vehicle	16.50m
Road train	
· lorry + 1 trailer	18.75m
· lorry + 2 trailers	22.00m
<b>Weight per axle</b>	
single non-drive axle	10.0t
single drive axle	11.5t
tandem axle, with a distance between the axles of	
· <1.00m	11.5t
· 1.00m to 1.30m	16.0t
· 1.30m to 1.80m	18.0t
· >1.80m	20.0t
tridem axle, with a distance between the axles of	
· <1.30m	21.0t
· 1.30m to 1.40m	24.0t
<b>Maximum permitted weight</b>	
Motor vehicle	
· with 2 axles	18.0t
· with 3 axles	25.0t
· with 4 axles	32.0t
Articulated vehicle	
· with 3 axles	28.0t
· with 4 axles	36.0t
· with 4 axles, and the weight of the tandem axle of the semi-trailer is 20t	38.0t
· with 5/6 axles	40.0t
· with 5/6 axles for the combined transport of a 40' ISO container	44.0t
Road train	
· with 4 axles	36.0t
· with 5/6 axles	40.0t

**Source:** UND, May 2015